

RTG 80130

SERIES II

Rough Terrain Crane 130-ton (120.0 mt)

- 41.4' ft to 162' ft (12.6 - 49.3 m) five-section formed full power latching boom with no charted capacity deductions for telescoping loads
- Five boom extend modes provided superior capacities: EM1-EM5
- Optional 31 ft to 55 ft (9.4 - 16.7 m) two-piece, bi-fold, on-board lattice attachment with 2°, 15°, 30°, and 45° manual offsets
- Optional 10 - 31 - 55 ft (3.0 - 9.4 - 16.7 m) three-piece, bi-fold, on-board lattice attachment with 2°, 15°, 30°, and 45° manual offsets, and 2° through 45° hydraulic offsets
- Optional three 18 ft (5.5 m) fly extensions plus 55 ft (16.7 m) provide a total attachment length of 109 ft (33.2 m)
- 278 ft (84.7 m) maximum tip height
- No deducts for stowed attachments
- 21,022 lbs (9 535.4 kg) maximum winch line pull
- 431 fpm (131.4 m/min) maximum winch line speed
- Electronic joystick controllers
- 6x2 and 6x6 drive with 23.5R25 tires
- Four steering modes: independent front, combination, crab, and independent rear
- Hydrostatic drive
- Fully independent double "A" arm hydraulic suspension

Link-Belt
C R A N E S

